



P-DUKE POWER

SDS05W · SDH05W Series


DC-DC Converter
Up to 5.04 Watts

3

YEARS
WARRANTY

ROHS
COMPLIANT

REACH
COMPLIANT



Automation



Datacom



IPC



Industry



Measurement



Telecom



Automobile



Boat



Charger



Medical



PV



Railway



3000
VDC
Isolation
Voltage

1600
VDC
Isolation
Voltage

4 : 1
Wide
Input
Range

NO
Min. Load
Required

REMOTE
ON
OFF

SCP

PART NUMBER STRUCTURE

SDS05 - 48

S

05

W

H

Series Name

Input
Voltage
(VDC)

Output
Quantity

Output
Voltage
(VDC)

Input
Range

Isolation
Options

SDS: SMD type
SDH: DIP type

24:9~36
48:18~75

S: Single

3P3:3.3
05:5
09:9
12:12
15:15
24:24

4:1

☐: Standard type
1600VDC isolation
H:3000VDC isolation

D: Dual

05:±5
12:±12
15:±15

TECHNICAL SPECIFICATION All specifications are typical at nominal input, full load and 25°C unless otherwise noted

Model Number	Input Range	Output Voltage	Output Current @Full Load	Input Current @ No Load	Efficiency	Maximum Capacitor Load
	VDC	VDC	mA	mA	%	μF
SDS(H)05-24S3P3W	9 ~ 36	3.3	1000	20	76	4400
SDS(H)05-24S05W	9 ~ 36	5	1000	30	80	2200
SDS(H)05-24S09W	9 ~ 36	9	555	30	81	1470
SDS(H)05-24S12W	9 ~ 36	12	420	30	83	1220
SDS(H)05-24S15W	9 ~ 36	15	333	30	83	1000
SDS(H)05-24S24W	9 ~ 36	24	210	30	83	470
SDS(H)05-24D05W	9 ~ 36	±5	±500	30	80	±1000
SDS(H)05-24D12W	9 ~ 36	±12	±210	30	83	±680
SDS(H)05-24D15W	9 ~ 36	±15	±168	30	84	±440
SDS(H)05-48S3P3W	18 ~ 75	3.3	1000	10	76	4400
SDS(H)05-48S05W	18 ~ 75	5	1000	12	81	2200
SDS(H)05-48S09W	18 ~ 75	9	555	15	81	1470
SDS(H)05-48S12W	18 ~ 75	12	420	15	83	1220
SDS(H)05-48S15W	18 ~ 75	15	333	15	83	1000
SDS(H)05-48S24W	18 ~ 75	24	210	15	83	470
SDS(H)05-48D05W	18 ~ 75	±5	±500	15	80	±1000
SDS(H)05-48D12W	18 ~ 75	±12	±210	15	83	±680
SDS(H)05-48D15W	18 ~ 75	±15	±168	15	84	±440

INPUT SPECIFICATIONS						
Parameter	Conditions		Min.	Typ.	Max.	Unit
Operating input voltage range	24Vin(nom) 48Vin(nom)		9 18	24 48	36 75	VDC
Start up time	Constant resistive load	Power up Remote ON/OFF		10 10	20 20	ms
Input surge voltage	1 second, max.	24Vin(nom) 48Vin(nom)			50 100	VDC
Input reflected ripple current	With external components.	24Vin(nom) 48Vin(nom)		20 15		mAp-p
Input filter			Capacitor type			
Remote ON/OFF	Ctrl pin applied current via 1kΩ	DC-DC ON	Open or high impedance			mA
		DC-DC OFF	2.0	3.0	4.0	mA
	Remote off input current				2.5	mA
	Application circuit DC-DC ON		DC-DC OFF			
						

OUTPUT SPECIFICATIONS						
Parameter	Conditions		Min.	Typ.	Max.	Unit
Voltage accuracy			-1.0		+1.0	%
Line regulation	Low Line to High Line at Full Load		-0.2		+0.2	%
Load regulation	No Load to Full Load	Single	-1.0		+1.0	%
		Dual	-1.0		+1.0	
	10% Load to 90% Load	Single	-0.5		+0.5	
		Dual	-0.8		+0.8	
Cross regulation	Asymmetrical load 25%/100% FL		-5.0		+5.0	%
Ripple and noise	Measured by 20MHz bandwidth			75		mVp-p
Temperature coefficient			-0.02		+0.02	%/°C
Transient response recovery time	25% load step change			500		μs
Short circuit protection			Continuous, automatic recovery			

GENERAL SPECIFICATIONS						
Parameter	Conditions		Min.	Typ.	Max.	Unit
Isolation voltage	1 minute	Standard Suffix "H"	1600 3000			VDC
Isolation resistance	500VDC		1			GΩ
Isolation capacitance		Standard Suffix "H"			50 50	pF
Switching frequency			100			kHz
Safety meets					IEC/ EN/ UL62368-1	
Case material					Non-conductive black plastic	
Base material					Non-conductive black plastic	
Potting material					Silicone (UL94 V-0)	
Weight					2.7g (0.10oz)	
MTBF	MIL-HDBK-217F, Full load				2.281 x 10 ⁶ hrs	


ENVIRONMENTAL SPECIFICATIONS						
Parameter	Conditions		Min.	Typ.	Max.	Unit
Operating ambient temperature	With derating		-40		+105	°C
Maximum case temperature					105	°C
Storage temperature range			-55		+125	°C
Thermal shock					MIL-STD-810F	
Vibration					MIL-STD-810F	
Relative humidity					5% to 95% RH	
Lead-free reflow solder process	Only for SMD type				IPC J-STD-020E	
Moisture sensitivity level(MSL)	Only for SMD type				IPC J-STD-033C Level 2	

EMC SPECIFICATIONS


Parameter	Conditions		Level
EMI	EN55032	With external components.	Class A, Class B
EMS	EN55024		
ESD	EN61000-4-2	Air $\pm 8\text{kV}$ and Contact $\pm 6\text{kV}$	Perf. Criteria A
Radiated immunity	EN61000-4-3	10 V/m	Perf. Criteria A
Fast transient	EN61000-4-4	$\pm 2\text{kV}$	Perf. Criteria A
Surge	EN61000-4-5	With an external input filter capacitor (Nippon chemi-con KY series, 220 $\mu\text{F}/100\text{V}$)	Perf. Criteria A
		$\pm 1\text{kV}$	
Conducted immunity	EN61000-4-6	10 Vr.m.s	Perf. Criteria A
Power frequency magnetic field	EN61000-4-8	100A/m continuous; 1000A/m 1 second	Perf. Criteria A

CAUTION: This power module is not internally fused. An input line fuse must always be used.


CHARACTERISTIC CURVE



SDS(H)05-48S05W Derating Curve



SDS(H)05-48S05W Efficiency vs. Input Voltage



SDS(H)05-48S05W Efficiency vs. Output Current

FUSE CONSIDERATION

This power module is not internally fused. An input line fuse must always be used.

This encapsulated power module can be used in a wide variety of applications, ranging from simple stand-alone operation to an integrated part of sophisticated power architecture.

To maximum flexibility, internal fusing is not included; however, to achieve maximum safety and system protection, always use an input line fuse.


The input line fuse suggest as below :

Modules	Fuse Rating (A)	Fuse Type
SDS(H)05-24S□□W、SDS(H)05-24D□□W	1.25	Slow-Blow
SDS(H)05-48S□□W、SDS(H)05-48D□□W	0.63	Slow-Blow

The table based on the information provided in this data sheet on inrush energy and maximum DC input current at low Vin..

MECHANICAL DRAWING

SDS05W: SMD TYPE




PIN CONNECTION

PIN	SINGLE	DUAL
1	+Vin	+Vin
2	-Vin	-Vin
4	Ctrl	Ctrl
5	NC	-Vout
6	-Vout	Common
7	+Vout	+Vout


1. All dimensions in inch [mm]
2. Tolerance :x.xx±0.02 [x.x±0.5]
x.xxx±0.010 [x.xx±0.25]
4. Pin dimension tolerance ±0.004[0.10]

SDH05W: DIP TYPE




RECOMMENDED PAD LAYOUT

SMD TYPE



All dimensions in inch[mm]
Pad size(lead free recommended)
Top view pad:0.224x0.055[5.70x1.40]

DIP TYPE



All dimensions in inch[mm]
Pad size(lead free recommended)
Through hole 1.2.4.5.6.7: $\varnothing 0.035[0.90]$
Top view pad 1.2.4.5.6.7: $\varnothing 0.044[1.13]$
Bottom view pad 1.2.4.5.6.7:
Groove R0.035[0.90]L-0.071[1.80]

THERMAL CONSIDERATIONS

The power module operates in a variety of thermal environments.

However, sufficient cooling should be provided to help ensure reliable operation of the unit.


Heat is removed by conduction, convection, and radiation to the surrounding Environment.

Proper cooling can be verified by measuring the point as the figure below.

The temperature at this location should not exceed "Maximum case temperature".


When Operating, adequate cooling must be provided to maintain the test point temperature at or below "Maximum case temperature".

You can limit this Temperature to a lower value for extremely high reliability.



TOP VIEW

LEAD FREE REFLOW PROFILE For SMD Type



*The curves define the maximum peak reflow temperature permissible measured on pin1 or Vin pin.