


Low VF Bridge Rectifiers




Features

- UL recognition, file #E230084
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.



Mechanical Data

- **Package:** 6KBJ
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GBJU2506
Device marking code			GBJU2506
Repetitive peak reverse voltage	VRRM	V	600
Average rectified output current @60Hz sine wave, R-load	IO	A	With heatsink Tc =115°C 25.0
			Without heatsink Ta =25°C 4.5
Surge(non-repetitive)forward current @60Hz half sine wave, 1 cycle, Tj=25°C	IFSM	A	360
Surge(non-repetitive)forward current @60Hz half sine wave, 1 cycle, Tj=125°C			260
Surge(non-repetitive)forward current @1ms, square wave, 1 time, Tj=25°C			720
Surge(non-repetitive)forward current @1ms, square wave, 1 time, Tj=125°C			500
Current squared time @1ms≤t≤8.3ms Tj=25°C, Rating of per diode	I ² t	A ² S	538
Storage temperature	Tstg	°C	-55 ~+150
Junction temperature	Tj	°C	-55 ~+150
Dielectric strength @ terminals to case, AC 1 minute	Vdis	KV	2.5
Mounting torque @recommend torque: 5kg·cm	Tor	kg·cm	8



GBJU2506

■Electrical Characteristics (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V _F	V	I _{FM} =12.5A T _j =25℃	-	0.87	0.92
Junction capacitance	C _j	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C.	170	190	210
DC reverse current at rated DC blocking voltage per diode	I _{RRM}	μA	V _{RM} =V _{RRM} T _j =25℃	-	0.5	5.0
Reverse Recovery time	T _{RR}	ns	I _F =0.5A I _R =1A I _{RR} =0.25A	3000		

■Thermal Characteristics (T_a=25℃ Unless otherwise specified)



PARAMETER		SYMBOL	UNIT	GBJU2506
Thermal Resistance	Between junction and ambient, Without heatsink	R _{θJ-A}	℃/W	22.0
	Between junction and case, With heatsink	R _{θJ-C}		0.8
	Between junction and Lead With heatsink	R _{θJ-L}		5.0






Note: Unit Mounted on 100mm*50mm*5mm+8*100mm*18mm*1.67mm aluminum Plate Heatsink

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GBJU2506	B1	Approximate 6.5	15	750	1500	TUBE


■ Characteristics(Typical)







■ Outline Dimensions



6KBJ		
Dim	Min	Max
A	29.7	30.3
B	19.7	20.3
C	17.0	18.0
D	4.8	5.8
E	3.8	4.2
F	7.3	7.7
G	9.8	10.2
H	0.9	1.1
I	2.0	2.4
J	2.3	2.7
K	3.4	3.8
L	4.4	4.8
M	10.8	11.2
N	3.1	3.7
O	3.1	3.4
P	0.6	0.8



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.