





Bridge Rectifier

Features

- UL recognition, file #E230084
- Ideal for printed circuit boards
- High surge current capability
- Low VF
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave Rectification for monitor, TV, printer, power supply, switching mode power supply, adapter, audio equipment, and home appliances applications.



Mechanical Data

- **Package:** GBU
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GBUU1506
Device marking code			GBUU1506
Repetitive peak reverse voltage	V_{RRM}	V	600
Average rectified output current @60Hz sine wave, R-load	With heatsink $T_c = 120^\circ\text{C}$	I_O	15
	Without heatsink $T_a = 25^\circ\text{C}$		3.5
Surge(non-repetitive)forward current @60Hz half sine wave, 1 cycle, $T_j = 25^\circ\text{C}$	I_{FSM}	A	220
Surge(non-repetitive)forward current @1ms, square wave, 1 time, $T_j = 25^\circ\text{C}$			440
Current squared time @1ms≤t≤8.3ms $T_j = 25^\circ\text{C}$, Rating of per diode	I^2t	A^2S	200
Reverse Surge Current @20ms, $T_j = 25^\circ\text{C}$	SI	mA	6
Storage temperature	T_{stg}	°C	-55 ~+150
Junction temperature	T_j	°C	-55 ~+150
Dielectric strength @ terminals to case, AC 1 minute	V_{dis}	KV	2.5
Mounting torque @recommend torque: 5kg·cm	T_{or}	kg·cm	8.0



GBUU1506

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V _F	V	I _{FM} =7.5A T _j =25°C	-	0.88	0.92
			I _{FM} =7.5A T _j =125°C	-	0.77	-
DC reverse current at rated DC blocking voltage per diode	I _{RRM}	μA	V _{RM} =V _{RRM} T _j =25°C	-	0.5	10
Reverse Recovery time	T _{RR}	ns	I _F =0.5A I _R =1A I _{RR} =0.25A	-	-	500



■Thermal Characteristics (T_a=25°C Unless otherwise specified)






PARAMETER		SYMBOL	UNIT	GBUU1506
Thermal Resistance	Between junction and ambient, Without heatsink	R _{θJ-A}	°C/W	23.0
	Between junction and case, With heatsink	R _{θJ-C}		1.4
	Between junction and Lead With heatsink	R _{θJ-L}		5

■Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GBUU1506	B1	Approximate 6.5	15	750	1500	TUBE


■ Characteristics (Typical)







■ Outline Dimensions



GBU		
Dim	Min	Max
A	21.80	22.30
B	18.30	18.80
C	17.50	18.00
D	3.50	4.10
E	7.40	7.90
F	1.65	2.16
G	1.91	2.54
H	2.06	2.54
I	1.02	1.27
J	4.83	5.33
K	3.30	3.56
L	2.40	2.66
M	0.46	0.56



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.