



Bridge Rectifiers



Features

- UL recognition, file #E313149
- Ideal for automated placement
- High surge current capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

General purpose use in high frequency AC/DC bridge full wave rectification for SMPS, lighting ballast, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

Mechanical Data

- **Package:** ABS
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	RABS2	RABS4	RABS6	RABS8	RABS10
Device marking code				RABS2	RABS4	RABS6	RABS8	RABS10
Repetitive peak reverse voltage		VRRM	V	200	400	600	800	1000
Average rectified output current @60Hz sine wave, R-load, T _a =40°C	On Alumina Substrate	I _O	A	1.0				
	On glass-epoxi substrate			0.7				
Surge(non-repetitive)forward current @60Hz half sine wave, 1 cycle, T _j =25°C		I _{FSM}	A	30				
Current squared time @1ms≤t<8.3ms T _j =25°C, Rating of per diode		I ² t	A ² s	3.7				
Storage temperature		T _{stg}	°C	-55 ~+150				
Junction temperature		T _j	°C	-55 ~+150				

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	RABS2	RABS4	RABS6	RABS8	RABS10
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =0.5A	1.30				
Maximum Reverse Recovery Time	T _{rr}	ns	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	500				
Maximum DC reverse current at rated DC blocking voltage per diode	I _{RRM}	μA	V _{RM} =VRRM	10				



RABS2 THRU RABS10



■ Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	RABS2-RABS10
Thermal Resistance	Between junction and ambient, On alumina substrate	R _{θJ-A}	°C/W	62.5
	Between junction and ambient, On glass-epoxy substrate			123.0
	Between junction and lead	R _{θJ-L}		25.0

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
RABS2-RABS10	F1	Approximate 0.095	4000	8000	64000	13" reel
RABS2-RABS10	F5	Approximate 0.095	5000	10000	80000	13" reel

■ Characteristics (Typical)





RABS2 THRU RABS10







FIG.5: Diagram of circuit and Testing wave form of reverse recovery time






RABS2 THRU RABS10

■ Outline Dimensions



ABS		
Dim	Min	Max
A	4.30	4.50
B	6.00	6.40
C	3.90	4.10
D	4.90	5.10
E	1.25	1.45
F	1.60 Max	
G	0.60	0.70
H	0.15	0.25
I	0.30	0.80
J	0.02	0.15

■ Suggested pad layout



Dim	Min
P1	5.72
P2	4.00
Q1	1.00
Q2	0.90



RABS2 THRU RABS10

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.