




JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD

PDFNWB5×6-8L Plastic-Encapsulate MOSFETS

CJAC130SN04 N-Channel Power MOSFET

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
40 V	2.1mΩ@10V	130A



DESCRIPTION

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.


FEATURES

- Battery switch
- Load switch
- High density cell design for ultra low $R_{DS(ON)}$
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation

APPLICATIONS


- Networking
- Load Switch
- LED applications

MARKING



CJAC130SN04 = Part No.
Solid dot=Pin1 indicator.
XX=Code.

EQUIVALENT CIRCUIT



MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	40	V
Gate-Source Voltage	V_{GS}	+20/-12	V
Continuous Drain Current	$I_D^{①}$	130	A
Pulsed Drain Current	$I_{DM}^{②}$	520	A
Single Pulsed Avalanche Energy	$E_{AS}^{③}$	320	mJ
Power Dissipation	$P_D^{①}$	120	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}^{⑥}$	62.5	$^{\circ}\text{C/W}$
Thermal Resistance from Junction to Case	$R_{\theta JC}^{①}$	1.04	$^{\circ}\text{C/W}$
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55~+150	$^{\circ}\text{C}$

MOSFET ELECTRICAL CHARACTERISTICS

$T_a=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Off characteristics							
Drain-source breakdown voltage	V _{(BR) DSS}	V _{GS} = 0V, I _D =250μA		40			V
Zero gate voltage drain current	I _{DSS}	V _{DS} =40V, V _{GS} =0V	T _J =25 ℃			1	μA
			T _J =125 ℃			100	
Gate-body leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =+20V/-12V				±100	nA
On characteristics ④							
Gate-threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA		2.0	2.9	4.0	V
Static drain-source on-sate resistance	R _{DS(on)}	V _{GS} =10V, I _D =20A			2.1	2.5	mΩ
Forward transconductance	g _{FS}	V _{DS} =5V, I _D =20A			32		S
Dynamic characteristics ④ ⑤							
Input capacitance	C _{iss}	V _{DS} =20V,V _{GS} =0V, f =1MHz			3350	5200	pF
Output capacitance	C _{oss}				1100	1700	
Reverse transfer capacitance	C _{rss}				120	190	
Switching characteristics ④ ⑤							
Total gate charge	Q _g	V _{GS} =10V, V _{DS} =20V, I _D =70A			61	100	nC
Gate-source charge	Q _{gs}				15	25	
Gate-drain charge	Q _{gd}				14	26	
Turn-on delay time	t _{d(on)}	V _{DS} =20V,I _D =1A , V _{GS} =10V,R _G =6Ω			13		ns
Turn-on rise time	t _r				22		
Turn-off delay time	t _{d(off)}				55		
Turn-off fall time	t _f				85		
Drain-Source Diode Characteristics							
Drain-source diode forward voltage	V _{SD} ④	V _{GS} =0V, I _S =10A				1.2	V
Continuous drain-source diode forward current	I _S ①					130	A
Pulsed drain-source diode forward current	I _{SM} ②					450	A

Notes:

1. $T_C = 25^{\circ}\text{C}$ Limited only by maximum temperature allowed.

2. $P_W \leq 10\mu s$, Duty cycle $\leq 1\%$.







3. EAS condition: $V_{DD} = 25V, V_{GS} = 10V, L = 0.1mH, R_g = 25\Omega$ Starting $T_J = 25^{\circ}\text{C}$.

4. Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.



5. Guaranteed by design, not subject to production.

6. The value of $R_{\theta JA}$ is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_a = 25^{\circ}\text{C}$.


Typical Characteristics




Typical Characteristics



PDFNWB5x6-8L Package Outline Dimensions



PDFNWB5x6-8L Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

PDFNWB5×6 Tape and Reel


PDFNWB5×6-8L Embossed Carrier Tape




Packaging Description:
PDFNWB5×6-8L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 5,000 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
PDFNWB5×6-8L	6.30	5.30	1.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

PDFNWB5×6-8L Tape Leader and Trailer



PDFNWB5×6-8L Reel



Dimensions are in millimeter						
Reel Option	D	D1	D2	G	W1	W2
13"Dia	Ø330.00	100.00	13.00	1.90	17.60	12.40

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
5,000 pcs	13 inch	5,000 pcs	340×336×29	50,000 pcs	353×346×365