




JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD

SOP8 Plastic-Encapsulate MOSFETS

CJQ4459 P-Channel Power MOSFET

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
-30V	46mΩ@ -10V	-6.5A
	72mΩ@ -4.5V	



DESCRIPTION

The CJQ4459 combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$. This device is ideal for load switch and battery protection applications

APPLICATIONS

- Battery Switch
- Load Switch


MARKING



Front side

Q4459= Device code
Solid dot=Pin1 indicator
Solid dot = Green molding compound device,
if none, the normal device
YY=Date Code

Equivalent Circuit



MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	I_D	-6.5	A
Pulsed Drain Current	I_{DM}	-26	A
Single Pulsed Avalanche Energy	$E_{AS}^{(1)}$	14	mJ
Power Dissipation	P_D	1.4	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	89	$^{\circ}\text{C/W}$
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	-55 ~ +150	$^{\circ}\text{C}$
Lead Temperature for Soldering Purposes(1/8" from case for 10s)	T_L	260	$^{\circ}\text{C}$

(1). E_{AS} condition: $V_{DD}=-50\text{V}$, $L=0.1\text{mH}$, $R_G=25\Omega$, Starting $T_J = 25^{\circ}\text{C}$

MOSFET ELECTRICAL CHARACTERISTICS







$T_a=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Off characteristics						
Drain-source breakdown voltage	V _{(BR) DSS}	V _{GS} = 0V, I _D =-250μA	-30			V
Zero gate voltage drain current	I _{DSS}	V _{DS} =-30V, V _{GS} =0V			-1	μA
Gate-body leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
On characteristics (note1)						
Gate-threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250μA	-1.4	-2.0	-2.4	V
Static drain-source on-sate resistance	R _{DS(on)}	V _{GS} =-10V, I _D =-6.5A		26	46	mΩ
		V _{GS} =-4.5V, I _D =-5A		46	72	mΩ
Forward transconductance	g _{FS}	V _{DS} =-5V, I _D =-6.5A	6			S
Dynamic characteristics (note 2)						
Input capacitance	C _{iss}	V _{DS} =-15V,V _{GS} =0V, f =1MHz	415		625	pF
Output capacitance	C _{OSS}		70		130	
Reverse transfer capacitance	C _{rss}		40		90	
Switching characteristics (note 2)						
Total gate charge	Q _g	V _{DS} =-15V, V _{GS} =-10V, I _D =-6.5A	7.4		11	nC
Gate-source charge	Q _{gs}		1.3		1.9	
Gate-drain charge	Q _{gd}		1.3		3.1	
Turn-on delay time	t _{d(on)}	V _{DD} =-15V,I _D =-1A, V _{GS} =-10V,R _G =3Ω, R _L =2.5Ω		7.5		ns
Turn-on rise time	t _r			5.5		
Turn-off delay time	t _{d(off)}			19		
Turn-off fall time	t _f			7		
Gate Resistance	R _g	f =1MHz, V _{DS} =0V, V _{GS} =0V,	3.5	7.5	11.5	Ω
Drain-Source Diode Characteristics						
Drain-source diode forward voltage(note1)	V _{SD}	V _{GS} =0V, I _S =-1A			-1	V
Continuous drain-source diode forward current	I _S				-6.5	A
Pulsed drain-source diode forward current	I _{SM}				-26	A

Notes:

1. Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
2. Guaranteed by design, not subject to production.

Typical Characteristics




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.450	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.700	5.100	0.185	0.201
e	1.270 (BSC)		0.050 (BSC)	
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Rev. - 1.1

SOP8 Tape and Reel


SOP8 Embossed Carrier Tape




Packaging Description:
SOP8 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 2,500 units per 13" or 33cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).
ALL DIM IN mm

Dimensions are in millimeter										
Pkg type	a	B	C	d	E	F	P0	P	P1	W
SOP8	6.40	5.40	2.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

SOP8 Tape Leader and Trailer



SOP8 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
13"Dia	Ø330.00	100.00	13.00	R151.00	R56.00	R6.50	12.40	17.60

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
4,000 pcs	13 inch	8,000 pcs	360×360×65	64,000 pcs	565×380×390	