



**ISOCOM**  
COMPONENTS

## IS900



### DESCRIPTION

The IS900 consists of a GaAs infrared emitting diode optically coupled to a high speed output integrated Microprocessor Compatible Schmitt trigger detector, which provides hysteresis for noise immunity and pulse shaping.

### FEATURES


- High Data Rate, 1MHz typical (NRZ)
- Free from Latch Up and Oscillation
- Microprocessor Compatible Drive
- Logical Compatible Output sinks 16mA at 0.4V maximum
- Guaranteed On/Off Threshold Hysteresis
- Wide Supply Voltage Capability, compatible with all popular Logic Systems
- Operating Voltage Range  
 $V_{CC}$  3V to 16V
- Operating Temperature Range  
- 55°C to +100°C
- High AC Isolation voltage 5000V<sub>RMS</sub>
- Lead Free and RoHS Compliant

### APPLICATIONS

- Logic to Logic isolator
- Line Receiver - eliminate noise and transient problems
- Programmable Current Level Sensor
- AC to TTL Conversion - Square Wave Shaping
- Power Supply Digital Programming
- Computer Peripherals Interface

### ORDER INFORMATION

- Add G after PN for 10mm lead spacing
- Add SM after PN for Surface Mount
- Add SMT&R after PN for Surface Mount Tape & Reel



- 1 Anode
- 2 Cathode
- 3 NC
- 4  $V_O$
- 5 GND
- 6  $V_{CC}$

### ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ )

Stresses exceeding the absolute maximum ratings can cause permanent damage to the device. Exposure to absolute maximum ratings for long periods of time can adversely affect reliability.

#### Input

Forward Current	60mA
Reverse Voltage	6V
Power Dissipation	120mW

#### Output

Output Current	50mA
Output Voltage	16V
Supply Voltage	16V
Power Dissipation	150mW

#### Total Package

Isolation Voltage	5000V <sub>RMS</sub>
Total Power Dissipation	250mW
Operating Temperature	-55 to 100 °C
Storage Temperature	-55 to 150 °C
Lead Soldering Temperature (10s)	260°C

#### ISOCOM COMPONENTS 2004 LTD

Unit 25B, Park View Road West, Park View Industrial Estate  
Hartlepool, Cleveland, TS25 1PE, United Kingdom  
Tel : +44 (0)1429 863 609 Fax : +44 (0)1429 863 581  
e-mail : sales@isocom.co.uk  
<http://www.isocom.com>

#### ISOCOM COMPONENTS ASIA LTD

Hong Kong Office  
Block A, 8/F, Wah Hing Industrial Mansions  
36 Tai Yau Street, San Po Kong, Kowloon, Hong Kong  
Tel : +852 2995 9217 Fax : +852 8161 6292  
e-mail : sales@isocom.com.hk

**Truth Table**

LED	V <sub>O</sub>
ON	LOW
OFF	HIGH

**ELECTRICAL CHARACTERISTICS** (T<sub>A</sub> = 25°C, unless otherwise specified. Typical Values at T<sub>A</sub> = 25°C)

**INPUT**

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = 10mA		1.15	1.5	V
Reverse Current	I <sub>R</sub>	V <sub>R</sub> = 5V			10	μA
Terminal Capacitance	C <sub>IN</sub>	V = 0V, f = 1MHz		33		pF

**OUTPUT**

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Operating Voltage	V <sub>CC</sub>		3		15	V
Supply Current	I <sub>CC(off)</sub>	V <sub>CC</sub> = 5V, I <sub>F</sub> = 0mA		1.6	5	mA
High Level Output Current	I <sub>OH</sub>	I <sub>F</sub> = 0mA, V <sub>CC</sub> = V <sub>O</sub> = 15V			100	μA

## IS900

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ , unless otherwise specified, Typical Values at $T_A = 25^\circ\text{C}$ )

#### COUPLED

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Supply Current	$I_{CC(on)}$	$V_{CC} = 5V, I_F = 10mA$		1.6	5	mA
Low Level Output Voltage	$V_{OL}$	$V_{CC} = 5V, I_F = I_{F(on)} (max), R_L = 270\Omega$			0.4	V
Turn-On Threshold Current	$I_{F(on)}$	$V_{CC} = 5V, R_L = 270\Omega$			1.6	mA
Turn-Off Threshold Current	$I_{F(off)}$	$V_{CC} = 5V, R_L = 270\Omega$		1		mA
Hysteresis Ratio	$I_{F(off)}/I_{F(on)}$	$V_{CC} = 5V, R_L = 270\Omega$	0.5		0.9	
Turn-On Time	$t_{(on)}$	$V_{CC} = 5V, I_F = I_{F(on)} (max), R_L = 270\Omega$			4	$\mu s$
Fall Time	$t_f$			0.1		
Turn-Off Time	$t_{(off)}$				4	
Rise Time	$t_r$			0.1		

#### ISOLATION

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Isolation Voltage	$V_{ISO}$	R.H. $\leq 50\%$ , $t = 1 \text{ min}$	5000			$V_{RMS}$
Input - Output Resistance	$R_{I-O}$	$V_{I-O} = 500VDC$ ,		$10^{11}$		$\Omega$

Device is considered a two terminal device : pins 1, 2 and 3 are shorted together and pins 4, 5 and 6 are shorted together.




Fig 1 Forward Current vs Forward Voltage




Fig 2 Transfer Characteristics




Fig 3 Normalized Turn-On Current vs Supply Voltage




Fig 4 Normalized Turn-On Current vs Ambient temperature




Fig 5 Low Level Output Voltage vs Load Current






Fig 6 Supply Current vs Supply Voltage




**Switching Time Test Circuit and Waveform**

## IS900

### ORDER INFORMATION

IS900			
After PN	PN	Description	Packing quantity
None	IS900	Standard DIP6	65 pcs per tube
G	IS900G	10mm Lead Spacing	65 pcs per tube
SM	IS900SM	Surface Mount	65 pcs per tube
SMT&R	IS900SMT&R	Surface Mount Tape & Reel	1000 pcs per reel

### DEVICE MARKING



IS900 denotes Device Part Number  
 I denotes Isocom  
 Y denotes 1 digit Year code  
 WW denotes 2 digit Week code




**ISOCOM**  
COMPONENTS


## IS900

### PACKAGE DIMENSIONS in mm (inch)


#### DIP



#### G Form




#### SMD








## RECOMMENDED PAD LAYOUT FOR SMD (mm)



## TAPE AND REEL PACKAGING



Direction of feed from reel



Dimension No.	A	B	Do	D1	E	F
Dimension( mm)	10.4±0.1	7.5±0.1	1.5±0.1	1.5+0.1/-0	1.75±0.1	7.5±0.1
Dimension No.	Po	P1	P2	t	W	K
Dimension (mm)	4.0±0.15	12.0±0.1	2.0±0.1	0.35±0.03	16.0±0.2	4.5±0.1






## IR REFLOW SOLDERING TEMPERATURE PROFILE

One Time Reflow Soldering is Recommended.

Do not immerse device body in solder paste.



Profile Details	Conditions
<b>Preheat</b> <ul style="list-style-type: none"><li>- Min Temperature (<math>T_{smin}</math>)</li><li>- Max Temperature (<math>T_{smax}</math>)</li><li>- Time <math>T_{smin}</math> to <math>T_{smax}</math> (<math>t_s</math>)</li></ul>	150°C 200°C 60s - 120s
<b>Soldering Zone</b> <ul style="list-style-type: none"><li>- Peak Temperature (<math>T_P</math>)</li><li>- Time at Peak Temperature</li><li>- Liquidous Temperature (<math>T_L</math>)</li><li>- Time within 5°C of Actual Peak Temperature (<math>T_P - 5^\circ\text{C}</math>)</li><li>- Time maintained above <math>T_L</math> (<math>t_L</math>)</li><li>- Ramp Up Rate (<math>T_L</math> to <math>T_P</math>)</li><li>- Ramp Down Rate (<math>T_P</math> to <math>T_L</math>)</li></ul>	260°C 10s max 217°C 30s max 60s - 100s 3°C/s max 6°C/s max
Average Ramp Up Rate ( $T_{smax}$ to $T_P$ )	3°C/s max
Time 25°C to Peak Temperature	8 minutes max

## DISCLAIMER

Isocom Components is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing Isocom Components products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such Isocom Components products could cause loss of human life, bodily injury or damage to property.

In developing your designs, please ensure that Isocom Components products are used within specified operating ranges as set forth in the most recent Isocom Components products specifications.

The Isocom Components products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These Isocom Components products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation Instruments, traffic signal instruments, combustion control instruments, medical Instruments, all types of safety devices, etc... Unintended Usage of Isocom Components products listed in this document shall be made at the customer's own risk.

Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.

The products described in this document are subject to the foreign exchange and foreign trade laws.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Isocom Components for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of Isocom Components or others.

The information contained herein is subject to change without notice.