

电缆密封 - HC-B-G-M40-EC-AL - 1411441

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://download.phoenixcontact.com>)



EVO电磁兼容电缆密封件，带卡口式连接，B系列，M40尺寸，电缆直径：19 - 27 mm



关键商业数据

包装单位	1 STK
GTIN	 4 046356 932400
GTIN	4046356932400
Sales Key	BF7AAF

技术数据

尺寸

接合螺母扳手规格	43 mm
电缆外径	19 mm ... 27 mm

环境条件

保护等级	IP66
	IP67
	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
环境温度 (运行)	-40 °C ... 125 °C (静态)

概述

螺钉连接类型	M40
导线数	1
标识材料	压铸铝，抗腐蚀
外壳材料	压铸铝，抗腐蚀

电缆密封 - HC-B-G-M40-EC-AL - 1411441

技术数据

概述


螺钉连接材料	铝
压力螺钉材料	铜镀镍
密封材料	NBR
电缆密封材料	NBR
屏蔽	有
接合螺母紧固扭矩	10.00 Nm
颜色	银色

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	环保使用期限 = 50
	更多有害物质的详情，请参考“下载区”内的“制造商声明”

产品图

尺寸图



尺寸图

认证

认证

认证

UL 认证 / cUL 认证 / EAC / cULus 认证

防爆认证

认证详情

UL 认证		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E255026
-------	---	---	---------

电缆密封 - HC-B-G-M40-EC-AL - 1411441

认证

cUL认证



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

E255026

EAC



RU C-
DE.AI30.B.01102

cULus认证



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>