

1		2		3		4		5		6		7		8	
△12-XXBF1A-SL8001 XX: No. Of Pin				REV.	ECN NO.	DATE	SIGN	DESCRIPTION							
				B	LEN1480591	2014/08/11	Rita	Update Logo							
				C	C210561	2021/04/08	Vicky	△X4							
Sealing Nut Seal Clamp Ring Gasket Connector															
5P Pin Assignments Front View				40.5(Ref.) △B Amphenol 14.5				△Note: * RoHS Compliant * (△) Important Dimension * Waterproof rate: IPX8, mated 1m/24h * Connector Housing: Thermoplastic, Black * Pin: Copper alloy, Gold plated * Extension Nut: Thermoplastic, Black * Nut: Metal * O-Ring: Rubber, Green * Gasket: Rubber, Black * Clamp Ring: Thermoplastic, Black * Sealing Nut: Thermoplastic, Black * Seal: Rubber, Black, OD:Ø4.5mm-Ø6.5mm * One set unassembled in one pe bag							
UNIT:mm		△		TITLE				ITEM NO		DRAWN BY		DATE			
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 3:2		SIZE A4		SHEET 1 OF 1		O SEN, M12 A (1) CABLE W/O SR, F, I, FI SOLDER △		Rita		2014-08-11			
										DWG NO		DATE			
										C 12-XXBF1A-SL8001		2014-08-11			
REV. C		WC-REV. A.4		QC: Inspection item		CUSTOMER		APPROVED BY		DATE					
						ALTW		Wenmao		2014-08-11					
												W10814-03-0001A2			

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.