




REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/20	Vicky	Initial Released
B	C220472	2022/03/28	Vicky	$\triangle B$ X2

AB-BD XX HL-BDBR-QE XXX

$\triangle B$ XX: No. Of Pin

XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters

Note:

- * RoHS Compliant
- * ϕ Important dimension
- * C1
Waterproof rate: IPX8, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Outer Mold: Thermoplastic, Black
- * C2
Waterproof rate: IPX8, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
O-Ring: Rubber, Dark gray
Nut: Thermoplastic, Black
Outer Mold: Thermoplastic, Black
- * Cable: SJTW, 18#*3C, PVC Jacket, Black, OD8.0mm
- * Cable length tolerance: 0.5M < L $\leq$ 1M: +60/-0 mm
1M < L $\leq$ 3M: +120/-0 mm
3M < L $\leq$ 5M: +160/-0 mm
5M < L $\leq$ 10M: $\pm$ 100 mm
10M < L $\leq$ 20M: $\pm$ 200 mm
20M < L $\leq$ 30M: $\pm$ 300 mm
30M < L $\leq$ 99M: $\pm$ 500 mm

A	UNIT:mm	TITLE ACC, XLOK, B-5A, DB-ENDED MF		ITEM NO		DRAWN BY Vicky	DATE 2020-01-20
	TOLERANCE $\pm 0.5mm$	SCALE 1:2	SIZE A4	SHEET 1	OF 1	CHECKED BY Rita	DATE 2020-01-20
		REV. B	WC-REV. A.5	ϕ Inspection item		APPROVED BY Max	DATE 2020-01-20

Amphenol LTW
安費諾亮泰企業股份有限公司

W10814-03-0001A2