


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/20	Vicky	Initial Released
B	C220473	2022/03/28	Vicky	$\triangle B$ X2




AB-BD XX ML-BDFR-QE XXX

$\triangle B$ XX: No. Of Pin

XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters

Pin Out	3 White 白 2 Green 綠 1 Black 黑
	Pin # Wire
C2	 3P
C1	 3P
Pin Assignments Front View	



Note:

- * RoHS Compliant
- * $\odot$ Important dimension
- * C1
Waterproof rate: IPX8, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Outer Mold: Thermoplastic, Black
- * C2
Waterproof rate: IPX8, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
O-Ring: Rubber, Dark gray
Nut: Thermoplastic, Black
Outer Mold: Thermoplastic, Black
- * Cable: SJTW, 18#*3C, PVC Jacket, Black, OD8.0mm
- * Cable length tolerance: 0.5M < L $\leq$ 1M: +60/-0 mm
1M < L $\leq$ 3M: +120/-0 mm
3M < L $\leq$ 5M: +160/-0 mm
5M < L $\leq$ 10M: $\pm$ 100 mm
10M < L $\leq$ 20M: $\pm$ 200 mm
20M < L $\leq$ 30M: $\pm$ 300 mm
30M < L $\leq$ 99M: $\pm$ 500 mm

UNIT:mm		TITLE	ACC, XLOK, B-5A, DB-ENDED MF	ITEM NO	DRAWN BY	DATE
TOLERANCE	$\pm 0.5mm$	SCALE	1:2	DWG NO	CHECKED BY	DATE
		SIZE	A4	AB-BDXXML-BDFR-QEXXX	Rita	2020-01-20
		SHEET	1 OF 1	CUSTOMER	APPROVED BY	DATE
		REV.	B	ALTW	Max	2020-01-20
		WC-REV.	A.5			
		$\odot$	Inspection item			

Amphenol LTW
安費諾亮泰企業股份有限公司