


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/02/03	Vicky	Initial Released
B	C220642	2022/04/29	Ruru	△B X2



C2

AB-CBD XX FR-CBDHL-QF XXX




XX: No. Of Pin


XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters

Note: △B

- * RoHS Compliant
- * L Important dimension
- * C1
Waterproof rate: IPX8, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper Alloy, Gold Plated
O-Ring: Rubber, Gray
Nut: Thermoplastic, Black
Outer mold: Thermoplastic, Black
- * C2
Waterproof rate: IPX8, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper Alloy, Gold Plated
Outer mold: Thermoplastic, Black
- * Cable: UL21996, 16#*3C+(26#*2P+D+AL/MY)+AL/MY, OD=11.0mm, PVC Jacket, Black
- * Cable length tolerance: 0.5M < L ≤ 1M: +60/-0 mm
1M < L ≤ 3M: +120/-0 mm
3M < L ≤ 5M: +160/-0 mm
5M < L ≤ 10M: ±100 mm
10M < L ≤ 20M: ±200 mm
20M < L ≤ 30M: ±300 mm
30M < L ≤ 99M: ±500 mm



C2
Pin Assignments
Front View



C1
Pin Assignments
Front View

8	Drain (26AWG)	地線	Twist 對線
7	Blue (26AWG)	藍	
6	Red (26AWG)	紅	
5	Green (26AWG)	綠	Twist 對線
4	White (26AWG)	白	
3	Black (16AWG)	黑	
2	Green (16AWG)	綠	
1	White (16AWG)	白	
C1 & C2		Wire Color	
Pin Out			

UNIT:mm		TOLERANCE		TITLE	
±0.5mm				ACC, XLOK, C-10A+5A, DB-ENDED FM	
SCALE	33:100	SIZE	A4	SHEET	1 OF 1
REV.	B	WC-REV.	A.5	L Inspection item	

Amphenol LTW		ITEM NO		DRAWN BY		DATE	
安費諾亮泰企業股份有限公司		DWG NO		Vicky		2020-02-03	
		AB-CBDXXFR-CBDHL-QFXXX		CHECKED BY		DATE	
				Rita		2020-02-03	
		CUSTOMER		APPROVED BY		DATE	
		ALTW		Max		2020-02-03	