





THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/02/03	Vicky	Initial Released
B	C220642	2022/04/29	Ruru	$\triangle$ B X2



AB-CBD XX HL-CBDBR-QF XXX
XX: No. Of Pin
XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters



8	Drain (26AWG)	地線	
7	Blue (26AWG)	藍	Twist 對線
6	Red (26AWG)	紅	
5	Green (26AWG)	綠	Twist 對線
4	White (26AWG)	白	
3	Black (16AWG)	黑	
2	Green (16AWG)	綠	
1	White (16AWG)	白	
C1 & C2	Wire Color		
	Pin Out		

Note: $\triangle$ B
* RoHS Compliant
* $\odot$ Important dimension
* C1
Waterproof rate: IPX8, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper Alloy, Gold Plated
Outer mold: Thermoplastic, Black
* C2
Waterproof rate: IPX8, mated 1m/24h
Housing: Thermoplastic, Black
Pin: Copper Alloy, Gold Plated
O-Ring: Rubber, Gray
Nut: Thermoplastic, Black
Outer mold: Thermoplastic, Black
* Cable: UL21996, 16#*3C+(26#*2P+D+AL/MY)+AL/MY, OD=11.0mm, PVC Jacket, Black
* Cable length tolerance: 0.5M < L ≤ 1M: +60/-0 mm
1M < L ≤ 3M: +120/-0 mm
3M < L ≤ 5M: +160/-0 mm
5M < L ≤ 10M: ±100 mm
10M < L ≤ 20M: ±200 mm
20M < L ≤ 30M: ±300 mm
30M < L ≤ 99M: ±500 mm

UNIT:mm		TITLE	ACC, XLOK, C-10A+5A, DB-ENDED MF	Amphenol LTW	ITEM NO	DRAWN BY	DATE
TOLERANCE	±0.5mm	SCALE	33:100	SIZE	A4	CHECKED BY	DATE
REV.	B	WC-REV.	A.5	SHEET	1 OF 1	APPROVED BY	DATE
			$\odot$ Inspection item	安費諾亮泰企業股份有限公司	CUSTOMER	Max	DATE
					ALTW		2020-02-03