



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-8A0101	2008/09/16	Shin	Add Note
C	LEN1640068	2016/03/30	Vicky	Update Logo
D	CI90268	2019/02/18	Ruru	Modify Note








PCB Layout



Recommended Panel Cut-Out



Pin Assignments
Front View



Note:

- * Important Dimension To Check
- * Waterproof Rate: IP67, Unmated
- * Housing: Thermoplastic, Black
- * Pin: Copper Alloy, Gold Plated
- * Nut: Thermoplastic, Black
- * Gasket: Rubber, Black

- * Use with waterproof cap or dust cap
Panel Thickness Max: 4.0mm
- * Use without waterproof cap or dust cap
Panel Thickness Max: 5.0mm
- * Gasket and Nut are packed separately
in PE bags.

UNIT:mm		TOLERANCE		TITLE		ITEM NO		DRAWN BY		DATE	
.X ±0.25		.XX ±0.1		Mini		AD-03PMMP-SS7001		Ruru		2019-02-18	
.XXX ±0.05		ANGLES ±1°		Panel Screw 3Pin M Conn. M Pin		DWG NO		Rita		2019-02-18	
REV. D		WC-REV. A.2		SCALE 2:1		CUSTOMER		Max		2019-02-18	
				SHEET 1 OF 1		ALTW					
				QC: Inspection item							

Amphenol LTW
安費諾亮泰企業股份有限公司