

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C190411	2019/03/14	Vicky	Change Note
C	C220466	2022/04/13	Ruru	$\triangle C \times 5$

Recommended
Panel Cut-out

$\triangle C$
BB-XXRMFS-QC800I
XX: No. Of Pin

$\triangle C$

Pin Assignment Front View

Note: $\triangle B \triangle C$
* RoHS Compliant
* $\odot\odot$ Important dimension
* Waterproof rate: IPX8, unmated 1m/24h
* Connector Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
* Nut: Thermoplastic, Black
* Gasket: Rubber, Gray
* For panel thickness max: 4.5mm
* Gasket and nut are packed separately in pe bag

UNIT:mm TOLERANCE . X ± 0.25 mm	TITLE XLOK, B-10A, REAR FASTENED M, F, SOLDER, PUSH LOCK $\triangle C$ SCALE 2:1 SIZE A4 SHEET I OF I REV. C WC-REV. A.3 $\odot\odot$: Inspection item	Amphenol LTW 安費諾亮泰企業股份有限公司	ITEM NO BB-XXRMFS-QC800I $\triangle C$ CUSTOMER ALTW DWG NO DRAWN BY Vicky CHECKED BY Rita APPROVED BY Max DATE 2019-03-14 DATE 2019-03-14 DATE 2019-03-14
---	--	--	--