





REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1580284-86	2015/08/12	Lu Di	Change To Common Drawing
C	LEN1680345 LEN1680352-53	2016/08/08	Mafei	Updated The Pin Out Color.



Note :

- *  Important Dimension To Check.
- * Waterproof Rate: IP67
- * Housing: M-PPE , Black.
- * Female Pin: Copper Alloy, Gold Plated.
- * Cable: UL2464 16#,PVC Jacket ,UV Resistant,Black.
- * Cable Length Tolerance: 01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm

* Prohibiting the use of place in oils

CB-02AMFM-RL7AXX	Ø 7.8
CB-03AMFM-RL7AXX	Ø 7.5
CB-04AMFM-RL7AXX	Ø 7.5
Part No.	Cable OD

UNIT: mm		TITLE MIDDLE CABLE RBL M CONN F PIN		
TOLERANCE	±0.5	SCALE 3:4	SIZE A4	SHEET 1 OF 2
		REV. C	WC-REV. A.3	QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Mafei	2016/08/08
DWG NO	CHECKED BY	DATE
CB-XXAMFM-RL7AXX	Joyy	2016/08/08
CUSTOMER	APPROVED BY	DATE
ALTW	Jerry	2016/08/08

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



CB-XXAMFM-RL7A XX

Middle Size Current Rating 10A

XX:No. Of Pin(Pin 數)

A:Cable With S/R(線端帶網尾)

M:Male Connector(公座)

F:Female Pin(母Pin)

M:Molding Type(射出成型)

XX:01~99Meter

01:01Meter

02:02Meter

...

...


99:99Meter




A:UL 2464 Cable

7:IP67(防水等級 67)

L:Straight(180°)

R:Snap In With Latch(彈臂卡合式)



Pin Out	4 -- 3 Red 紅 2 -- 1 Black 黑	4 Green 綠 3 White 白 2 -- 1 Black 黑	4 Orange 橙 3 Red 紅 2 Brown 棕 1 Black 黑
Pin Assignments Front View	 2Pin	 3Pin	 4Pin

UNIT:mm TOLERANCE ±0.5	TITLE MIDDLE CABLE RBL M CONN F PIN			Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO	DRAWN BY Mafei	DATE 2016/08/08
	SCALE 3:4	SIZE A4	SHEET 2 OF 2			DWG NO CB-XXAMFM-RL7AXX	CHECKED BY Joyy	DATE 2016/08/08
	REV. C	WC-REV. A.3	QC:Inspection item			CUSTOMER ALTW	APPROVED BY Jerry	DATE 2016/08/08