

1	2	3	4	5	6	7	8	THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.
F				REV. A	ECN NO. Initial Release	DATE 2014/06/25	SIGN Tom gu	
E				B	C200210	2020/02/25	Ruru	
D							DESCRIPTION Change Rev.1 To Rev.A	
C							BX4	
B								
A								

ALTW
CONFIDENTIAL
2020.02.25
R&D DEPT.

① Half-Finished Goods

② Seals(OD7.8~9.3mm)

③ Sealing Nut

(Please See the Condition 1 & 2)
兩螺絲孔無防水功能(需挖盲孔)
6-32UNC*2

壓迫區域 Gasket
Gasket 壓迫區域

ø14.0±0.1
最小挖孔尺寸,
最大不得超出

Recommended
Panel Cut-Out

Condition 1

Condition 2

Note:

- * @Important Dimension.
- * Waterproof Rating: IP67
- * Cable OD: ø7.8~ø9.3mm
- * Gasket. Seals: Rubber, Gray.
- * O-ring: Rubber, Gray.
- * Body&Sealing Nut: Thermoplastic, Black.
- * Screw & Washer:Stainless Steel,Silver.
- * 螺絲與對插板對鎖後, 對插板距本體之均勻距離 0.8mm 為達到 IP67 防水狀態
- * ①②③ 組裝後放入一個 PE 袋
- < Sealing Nut 鎖 2~3 牙即可>

UNIT:mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE
CABLE GLAND, OD14, PC
7.8, 9.3, BK

SCALE Free

SHEET 1 OF 1

REV. B

SIZE A4

QC :Inspection Item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO CSF-D14002

DWG NO CSF-D14002

CUSTOMER ALTW

DRAWN BY Tom

CHECKED BY Ludi

APPROVED BY Victor

DATE 2014/06/28

DATE 2014/06/28

DATE 2014/06/28