







REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2014/06/28	Tom gu	Change Rev.1 To Rev.A

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

兩螺絲孔無防水功能(需挖盲孔)
(Please See the Condition 1 & 2)
6-32UNC*2



- Note:
- * Waterproof Rate:IP67.
 - * Cable OD:ø5.5~ø7.0mm.
 - * Tempertaure Rating:-40°C~+85°C.
 - * Gasket. Seals:Silicone,Gray.
 - * O-ring:Silicone,Gray.
 - * Body & Sealing Nut:ZDC-3,Nickel Plated 120u".
 - * Screw & Washer:Stainless Steel.
 - * Sealing Nut Torque:12~16 kgf.cm
 - * 螺絲與對插板對鎖後,對插板距本體之均勻距離 0.8mm 為達到 IP67 防水狀態
 - * ①②③組裝後放入一個 PE 袋 (Sealing Nut鎖 2~3 牙即可)

UNIT:mm		TITLE
TOLERANCE	±0.5 mm	RJ Ass'y (OD5.5~7.0mm) (After Plug In)
SCALE	Free	SHEET 1 OF 1
REV. A	SIZE A4	QC :Inspection Item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	CSF-D14003	DRAWN BY	Tom	DATE	2014/06/28
DWG NO	CSF-D14003	CHECKED BY	Ludi	DATE	2014/06/28
CUSTOMER	ALTW	APPROVED BY	Victor	DATE	2014/06/28