

REV.		ECN NO.		DATE		SIGN		DESCRIPTION	
B		LEN1660033		2016/05/27		Vicky		Update Dime	
C		C190403		2019/03/13		Vicky		Change Note	
D		C220628		2022/05/12		Vicky		D X4	

23.6 ± 0.1

25.6 ± 0.1

Recommended Panel Cut-Out

17.9

3.7

25.4 ± 0.4

1"-20 UNEF

28.5 (Hex.)

33.0 (Ref.)

32.0

23.2

14P

18P

Pin Assignments Front View

UNIT: mm

TOLERANCE

.X ± 0.25

.XX ± 0.1

.XXX ± 0.05

ANGLES ± 1°

TITLE

XLOK, D-5A, REAR FASTENED

M, M, SOLDER, PUSH LOCK

SCALE 3:2

SIZE A4

SHEET 1 OF 1

REV. D

WC-REV. A.2

QC: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO.

DWG. NO.

CUSTOMER

ALTW

DRAWN BY

Vicky

CHECKED BY

Rita

APPROVED BY

Max

DATE

2019-03-13

DATE

2019-03-13

DATE

2019-03-13

DD-XXRMMS-QC8001

XX: No. Of Pin

White Printing

Connector

Gasket

Nut

Note:

- * RoHS Compliant
- * Important dimension
- * Waterproof rate: IPX8, unmated 1m/24h
- * Connector
- Housing: Thermoplastic, Black
- Pin: Copper Alloy, Gold plated
- * Nut: Thermoplastic, Black
- * Gasket: Rubber, Gray
- * For panel thickness max: 3.6mm
- * Gasket and nut are packed separately in pe bag