

1		2		3		4		5		6		7		8									
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION											
				A		Initial Release		2010/04/22		Jessie		Form Rev.03 To A											
				B		C210669		2021/04/27		Vicky		△B X5											
				C		C221869		2022/12/05		Vicky		△C X1											
				△B HC20-XXBFMA-SL8001 XX: No. Of Pin																			
				△B Note: * RoHS Compliant * △C Important dimension * Waterproof rate: IP68, mated 1m/24h * Connector - Housing: Metal - Pin: Copper alloy, Gold plated - Gasket: Rubber, Gray - Nut: Metal * Body: Metal * Sealing Nut: Metal * Seal1: Rubber, Gray, OD Ø5.5mm~7.0mm * Seal2: Rubber, Gray, OD Ø7.0mm~9.3mm * Seal3: Rubber, Gray, OD Ø9.3mm~12.5mm * One set assembled in one pe bag																			
				△B Pin Assignments Front View																			
				△B UNIT:mm TOLERANCE <table><tr><td>.X</td><td>±0.25</td></tr><tr><td>.XX</td><td>±0.1</td></tr><tr><td>.XXX</td><td>±0.05</td></tr><tr><td>ANGLES</td><td>±1°</td></tr></table>												.X	±0.25	.XX	±0.1	.XXX	±0.05	ANGLES	±1°
.X	±0.25																						
.XX	±0.1																						
.XXX	±0.05																						
ANGLES	±1°																						
				△B TITLE O SEN, M20 500H,20A CABLE W/O SR, F, M, FI SOLDER SCALE 1:1 SIZE A4 SHEET 1 OF 1 REV. C WC-REV. A.2 △C Inspection item																			
				Amphenol LTW 安費諾亮泰企業股份有限公司																			
				ITEM NO DWG NO △B HC20-XXBFMA-SL8001 CUSTOMER ALTW DRAWN BY Jessie CHECKED BY Jimmy APPROVED BY Win DATE 2010-04-22 DATE 2010-05-12 DATE 2010-05-12																			
				8 W10814-03-0001A2																			