

1		2		3		4		5		6		7		8					
△ MI2A-XXBFFA-SL7001 XX: No. Of Pin				REV.	ECN NO.	DATE	SIGN	DESCRIPTION											
				B	LEN1670554	2016/07/22	Yulong_wang	Change the Note											
				C	C201453	2020/10/07	Ruru	△C X5											
				D	C210561	2021/04/08	Vicky	△D X2											
Connector Clamp Ring Seal Sealing Nut																			
△ 16.0 Hex. (Metal Nut)				47.0(Ref.) 18.6 Amphenol 16.0 Hex.															
△ 10P 12P Pin Assignments Front View																			
UNIT:mm △ TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°				TITLE N SEN, MI2 A, SCREW CABLE W/O SR, F, F, FI SOLDER △C SCALE 1:1 SIZE A4 SHEET 1 OF 1 REV. D WC-REV. A.3 QC:Inspection item				ITEM NO DWG NO △MI2A-XXBFFA-SL7001 CUSTOMER ALTW				DRAWN BY Yulong_wang CHECKED BY Jinhai APPROVED BY Jerry				DATE 2016-07-22 DATE 2016-07-22 DATE 2016-07-22			
				Amphenol LTW 安費諾亮泰企業股份有限公司															
		2		3		4		5		6		7		8					

△C△D
Note:
* RoHS Compliant
* Ⓞ Important Dimension
* Waterproof rate: IPX7, mated
* Connector
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Extension Nut: Thermoplastic, Black
Nut: Metal
O-Ring: Rubber, Gray
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
△B * Seal: Rubber, Gray, OD:Ø4.0mm~Ø8.0mm
* One set unassembled in one pe bag

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.