






REV.	ECN NO.	DATE	SIGN	DESCRIPTION
D	C201473	2020/09/24	Vicky	X3
E	C210024	2021/01/18	Vicky	X2
F	C210309	2021/02/26	Ruru	X2




MI2B-XXPMMP-SF8002


XX: No. Of Pin

Recommended
Panel Cut-Out

3P




4P




5P


PCB Layout



3P



4P



5P

Pin Assignment Front View




Note:

- * RoHS Compliant
- * Important dimension
- * Waterproof rate: IPX8, unmated 1m/24h
IPX9K, unmated
- * Connector
- * Housing: Thermoplastic, Black
- * Pin: Copper alloy, Gold plated
- * Shield: Metal
- * Nut: Metal
- * O-Ring: Rubber, Black
- * For panel thickness max: 4.5mm
- * Nut is packed separately in pe bag



UNIT:mm



TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE

N SEN, MI2 B, SCREW
RECEPTACLE, M, M, PCB S

SCALE 3:2

SIZE A4

SHEET 1 OF 1

REV. F

WC-REV. A.5

Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

DWG. NO

MI2B-XXPMMP-SF8002

CUSTOMER

ALTW

DRAWN BY

Yulong_wang

CHECKED BY

Jinhai

APPROVED BY

Jerry

DATE

2016-09-05

DATE

2016-09-05

DATE

2016-09-05