


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
D	C201473	2020/09/24	Vicky	X3
E	C210024	2021/01/12	Vicky	X2
F	C210309	2021/02/26	Ruru	X2






Recommended
Panel Cut-Out




MI2B-XXPMMS-SF8002

XX: No. Of Pin




Note:


- * RoHS Compliant
- * Important dimension
- * Waterproof rate: IPX8, unmated 1m/24h
IPX9K, unmated
- * Connector
- Housing: Thermoplastic, Black
- Pin: Copper alloy, Gold plated
- * Shield: Metal
- * Nut: Metal
- * O-Ring: Rubber, Black
- * For panel thickness max: 4.5mm
- * Nut is packed separately in pe bag



3P




4P



5P

Pin Assignment Front View

UNIT:mm



TITLE

N SEN, MI2 B, SCREW
RECEPTACLE, M, M, SOLDER

SCALE 2:1

SIZE A4

SHEET 1 OF 1

REV. F

WC-REV. A.5

: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

DWG. NO

MI2B-XXPMMS-SF8002

CUSTOMER

ALTW

DRAWN BY

Yulong_wang

CHECKED BY

Jinhai

APPROVED BY

Jerry

DATE

2016-09-05

DATE

2016-09-05

DATE

2016-09-05