

	1	2	3	4	5	6	7	8		
F	△D MI2D-XXBFFC-SL7001 XX: No. Of Pin				REV.	ECN NO.	DATE	SIGN	DESCRIPTION	
					D	C201469	2020/09/25	Ruru	△D X4	
					E	C210561	2021/04/12	Vicky	△E X2	
					F	C210977	2021/06/23	Vicky	△F X1	
E	Connector Clamp Ring Seal Sealing Nut									
D	47.0(Ref.) 16.0Hex. (Metal Nut) 16.0Hex.									
C	Note: * RoHS Compliant * ⌀ Important Dimension * Waterproof rate: IPX7, mated * Connector Housing: Thermoplastic, Black Pin: Copper alloy, Gold plated Extension Nut: Thermoplastic, Black Nut: Metal △D O-Ring: Rubber, Gray * Clamp Ring: Thermoplastic, Black * Sealing Nut: Thermoplastic, Black △C △E * Seal: Rubber, Gray, OD: $\varnothing 4.0\text{mm} \sim \varnothing 8.0\text{mm}$ * Applicable wire gauge: 20AWG~24AWG * One set unassembled in one pe bag									
B	4P Pin Assignments Front View PE Bag									
A	UNIT:mm	△D N SEN, MI2 D, SCREW CABLE W/O SR, F, F, FI/PANEL CRIMP			Amphenol LTW		ITEM NO		DRAWN BY	DATE
	TOLERANCE	SCALE			SIZE	SHEET	OF	DWG NO	CHECKED BY	DATE
	.X ±0.25	Free			A4	1	1	MI2D-XXBFFC-SL7001	Li-Feng	2019/12/17
	.XX ±0.1	REV.			WC-REV.	QC: Inspection item		CUSTOMER	APPROVED BY	DATE
	.XXX ±0.05	F			.0			ALTW	Jerry	2019/12/17
	ANGLES ±1°									
		2	3	4	5	6	7	8	W10814-03-0001A2	