

	1	2	3	4	5	6	7	8	
F	△MI2T-XXBFFB-SL7002 XX: No. Of Pin				REV.	ECN NO.	DATE	SIGN	DESCRIPTION
					C	C201549	2020/10/15	Vicky	△CX4
					D	C210025	2021/01/20	Vicky	△DX1
E					E	C210561	2021/04/19	Vicky	△EX2
D									
C									
B									
A									

4P

Pin Assignments Front View

UNIT:mm

TOLERANCE

.X ±0.25

.XX ±0.1

.XXX ±0.05

ANGLES ±1°

TITLE

N SEN, MI2 T, SCREW

CABLE W/O SR, F, F, FI SCREWIN

SCALE

1:1

SIZE

A4

SHEET

1

OF

1

REV.

E

WC-REV.

A.2

QC

: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

DWG NO

CUSTOMER

DRAWN BY

CHECKED BY

APPROVED BY

DATE

DATE

DATE

2018-02-01

2018-02-01

2018-02-01

ALTW

Jerry

Note:

* RoHS Compliant

*

⌀

 Important Dimension

* Waterproof rate: IPX7, mated

* Connector

△BHousing: Thermoplastic, Black

Pin: Copper alloy, Gold plated

Extension Nut: Thermoplastic, Black

△DNut: Metal

O-Ring: Rubber, Gray

* Clamp Ring: Thermoplastic, Black

* Sealing Nut: Thermoplastic, Black

* Seal: Rubber, Gray, OD:⌀8.0mm~⌀10.0mm

* One set unassembled in one pe bag

Connector

Clamp Ring

Seal

Sealing Nut

55.0(Ref.)

18.6

16.0 Hex.

(Metal Nut)

17.0 Hex.

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.