

1		2		3		4		5		6		7		8	
△MI2T-XXBMMB-SL7002 XX: No. Of Pin				REV.	ECN NO.	DATE		SIGN		DESCRIPTION					
				B	C201549	2020/10/15		Vicky		△BX4					
				C	C210025	2021/01/20		Vicky		△CX1					
				D	C210561	2021/04/19		Vicky		△DX2					
Connector Clamp Ring Seal Sealing Nut															
4P Pin Assignments Front View				58.5(Ref.) △20.1 MI2*1.0 16Hex. (Metal Nut) 17Hex.											
UNIT:mm TOLERANCE .X±0.25 .XX±0.1 .XXX±0.05 ANGLES±1°				TITLE N SEN, MI2 T, SCREW CABLE W/O SR, M, M, FI SCREW IN △△ SCALE 1:1 SIZE A4 SHEET 1 OF 1 REV. D WC-REV. A.1 QC:Inspection item				Amphenol LTW 安費諾亮泰企業股份有限公司 ITEM NO DWG NO △MI2T-XXBMMB-SL7002 CUSTOMER ALTW DRAWN BY Cary CHECKED BY Lu Di APPROVED BY Jerry DATE 2015-03-26 DATE 2015-03-26 DATE 2015-03-26							
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.															

△B△D
Note:
* RoHS Compliant
* △△ Important Dimension
* Waterproof rate: IPX7, mated
* Connector
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Extension Nut: Thermoplastic, Black
△C Nut: Metal
O-Ring: Rubber, Gray
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
* Seal: Rubber, Gray, OD:Ø8.0mm~Ø10.0mm
* One set unassembled in one pe bag