

1		2		3		4		5		6		7		8	
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				D		C201647		2020/10/23		Vicky		△D X5			
				E		C210561		2021/04/14		Vicky		△E X3			
				F		C210977		2021/06/23		Vicky		△F X1			
△D MSAP-XXBMMC-SL7001 XX: No. Of Pin M12*1.0 Connector Clamp Ring Amphenol Seal Sealing Nut 51.0(Ref.) △D 20.1 16.0 Hex. Amphenol 16.0Hex. 4P Pin Assignments Front View PE Bag UNIT:mm ±0.25 ±0.1 ±0.05 ±1° TOLERANCE ANGLES .X .XX .XXX △E △F △C N SEN, M12 A -PLASTIC, SCREW CABLE W/O SR, M, M, FI/PANEL CRIMP SCALE Free SIZE A4 SHEET 1 OF 1 REV. F WC-REV. .0 QC:Inspection item Amphenol LTW 安費諾亮泰企業股份有限公司 ITEM NO DWG NO CUSTOMER MSAP-XXBMMC-SL7001 ALTW DRAWN BY CHECKED BY APPROVED BY Xiaofeng Li-Feng Jerry DATE DATE DATE 2019/12/17 2019/12/17 2019/12/17 Note: * RoHS Compliant * ⌀ Important Dimension * Waterproof rate: IPX7, mated * Connector Housing: Thermoplastic, Black Pin: Copper alloy, Gold plated Extension Nut: Thermoplastic, Black Nut: Thermoplastic, Black △D O-Ring: Rubber, Gray * Clamp Ring: Thermoplastic, Black * Sealing Nut: Thermoplastic, Black △C Seal: Rubber, Gray, OD:⌀4.0mm~⌀8.0mm △F * Applicable wire gauge: 20AWG~24AWG * One set unassembled in one pe bag THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.															