

	1	2	3	4	5	6	7	8	
F	△MSBP-XXBFFA-SL8001 XX: No. Of Pin				REV.	ECN NO.	DATE	SIGN	DESCRIPTION
					B	C210561	2021/04/15	Vicky	△B X4
E	Sealing Nut Seal Clamp Ring Gasket Connector								
D	40.0 (Ref.) 12.90 (Hex.) Ø15.3								
C	△Note: * RoHS Compliant * △QC Important Dimension * Waterproof rate: IPX8, mated 1m/24h * Connector Housing: Thermoplastic, Black Pin: Copper alloy, Gold plated Extension Nut: Thermoplastic, Black Nut: Thermoplastic, Black O-Ring: Rubber, Gray * Gasket: Rubber, Gray * Clamp Ring: Thermoplastic, Black * Sealing Nut: Thermoplastic, Black * Seal: Rubber, Gray, OD:Ø4.5mm-Ø6.5mm * One set unassembled in one pe bag								
B	3P 4P 5P Pin Assignments Front View								
A	UNIT:mm	△ △		TITLE	ITEM NO		DRAWN BY	DATE	
	TOLERANCE	N SEN, MI2 B -PLASTIC, SCREW CABLE W/O SR, F, F, FI SOLDER		SCALE	MSBP-XXBFFA-SL8001		JC Chen	2019/08/28	
	.X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°	SIZE A4	SHEET 1 OF 1	WC-REV. A.5	CHECKED BY Li Feng	DATE 2019/08/28	APPROVED BY Jerry	DATE 2019/08/28	
	REV. B	△QC: Inspection item		CUSTOMER ALTW					
	2	3	4	5	6	7	8	W10814-03-0001A2	

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.