

1		2		3		4		5		6		7		8	
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				A		Initial Release		2015/10/12		Mila		Change Rev. I To Rev. A			
				B		C201524		2020/10/05		Vicky		△B X4			
				C		C210561		2021/04/15		Vicky		△C X3			
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.															
Connector Clamp Ring Seal Sealing Nut Amphenol Amphenol 5P Pin Assignments Front View MSBP-XXBMMB-SR7001 XX: No. Of Pin Top View Bottom View MI2*1.0 43.2(Ref.) Ø20.1 16.0 Hex. 16.0 Hex. 35.5(Ref.) Note: * RoHS Compliant * ⌀ Important Dimension * Waterproof rate: IPX7, mated * Connector Housing: Thermoplastic, Black Pin: Copper alloy, Gold plated Extension Nut: Thermoplastic, Black Nut: Thermoplastic, Black O-Ring: Rubber, Gray * Clamp Ring: Thermoplastic, Black * Sealing Nut: Thermoplastic, Black * Seal: Rubber, Gray, OD:Ø4.0mm~Ø7.0mm * One set unassembled in one pe bag UNIT:mm TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1° 1:1 A4 SHEET 1 OF 1 REV. C WC-REV. A.1 QC:Inspection item Amphenol LTW 安費諾亮泰企業股份有限公司 ITEM NO DWG NO CUSTOMER DRAWN BY CHECKED BY APPROVED BY DATE DATE DATE W10814-03-0001A2															