

1		2		3		4		5		6		7		8	
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				B		C201470		2020/10/06		Ruru		△X2			
				C		C210561		2021/04/16		Vicky		△C X2			
F															
E															
D															
C															
B															
A															

Connector

Clamp Ring

Seal

Sealing Nut

4P

Pin Assignments
Front View

△B
MSDP-XXBFFA-SR7001

XX: No. Of Pin

4P

Pin Assignments
Front View

UNIT:mm				TITLE	
				N SEN, MI2 D -PLASTIC, SCREW △C	
TOLERANCE				CABLE W/O SR, F, F, FI SOLDER	
.X	±0.25	SCALE	1:1	SIZE	A4
.XX	±0.1	REV.	C	WC-REV.	A.5
.XXX	±0.05	QC:Inspection item			
ANGLES	±1°				

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY		DATE	
		JC Chen		2020-04-17	
DWG NO		CHECKED BY		DATE	
△B MSDP-XXBFFA-SR7001		Li Feng		2020-04-17	
CUSTOMER		APPROVED BY		DATE	
ALTW		Jerry		2020-04-17	

39.3(Ref.)

18.6

16.0 Hex.

35.5(Ref.)

16.0 Hex.

△C

Note:

- * RoHS Compliant
- * △C Important Dimension
- * Waterproof rate: IPX7, mated
- * Connector
- Housing: Thermoplastic, Black
- Pin: Copper alloy, Gold plated
- Extension Nut: Thermoplastic, Black
- Nut: Thermoplastic, Black
- O-Ring: Rubber, Gray
- * Clamp Ring: Thermoplastic, Black
- * Sealing Nut: Thermoplastic, Black
- * Seal: Rubber, Gray, OD:Ø4.0mm-Ø7.0mm
- * One set unassembled in one pe bag

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.